U.S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communications Standard. 29CFR 1910.1200. Standard must be consulted for specific requirements.

| | | | SE | CTION I | | | | | | |
|--|----------------------|---------------|-------------------------------------|--------------------------|----------------|-------------------------------------|-------------|---------------------------------------|--|--|
| MANUFACTURER'S NAM | TELEPHONE NO. | | | | | | | | | |
| The Triad Group / Certified Safety Mfg., Inc. | | | | | (816) 483-9090 | | | | | |
| ADDRESS: | | | | | | | | | | |
| 1400 Chestnut Avenue | | Missouri 6 | 6412 | 27 | | | | | | |
| IDENTITY (AS USED ON LABEL): | | | | | | DATE PREPARED: | DATE | REVIEWED: | | |
| A | cohol Pads (| Nipes) | | | | 08/21/08 | | | | |
| SECTION II – HAZARDOUS INGREDIENTS/IDENTITY INFORMATION | | | | | | | | | | |
| HAZARDOUS COMPONENTS (Specific Chemical Identity; Common Name(s)): % OSHA PEL ACGIH TLV OTHER LIMITS RECOMMENDED | | | | | | | | | | |
| | | | | | | | | Omg/m ³) | | |
| (Isopropanol) | | | | ,, | | | | , , , , , , , , , , , , , , , , , , , | | |
| | | | | | | | | | | |
| THIS PRODU | ICT IS PRODU | JCED AS A | HEA | LTH CAF | RE ITE | M "FOOD, DRUG OR C | OSMET | TC, | | |
| | | | | | | EES WHILE IN THE W | | | | |
| | | | | | | JIREMENTS OF; 29CFF | | | | |
| (A) & (B) D | O NOT APPL | Y, AS SPEC | IFIC | ALLY ST | ATED | IN 29CFR 1910.1200 (E | 3) (5) (V |) | | |
| | | SECTION | J III . | _ PHYSIC | CAL D | ΔΤΔ | | | | |
| BOILING POINT (°F): | _18 | | | | | (H ₂ 0= 1): | | 0.878 | | |
| VAPOR PRESSURE (mm | | - | MELTING POINT: | | | | | N/A | | |
| VAPOR DENSITY (AIR=1 | • • | | EVAPORATION RATE (Butyl Acetate=1): | | | | | >7.0 | | |
| SOLUBILITY IN WATER: | | | | | | | | 7710 | | |
| | APPEARANCE AND ODOR: | | | | | | | | | |
| | Clea | ır, colorless | with | characte | ristic s | smell of IPA. | | | | |
| | SECTIO | V IV – FIRE | AND | EXPLO | SION | HAZARD DATA | | | | |
| FLASH POINT (Method used): 70° F (TAG Open Cup) FLAMMABLE LIMITS: LEL: 2% UEL: 12% | | | | | | | 2% | | | |
| EXTINGUISHING MEDIA | : Use water s | oray, water f | og, a | alcohol ty | pe foa | am, dry chemical or CO ₂ | , | | | |
| SPECIAL FIRE FIGHTING | G PROCEDUR | RES: Wear p | rope | er protecti | on. fic | aht fire from safe distanc | <u></u> | | | |
| SPECIAL FIRE FIGHTING PROCEDURES: Wear proper protection, fight fire from safe distance. UNUSUAL FIRE AND EXPLOSION HAZARDS: Releases vapor below ambient temperatures. Vapors may travel | | | | | | | | | | |
| Long distances before ign | | | | | | I | | , | | |
| | - y | 9 | | | | | | | | |
| | | SECTION | ٧ – | REACTI | VITY I | DATA | | | | |
| STABILITY: | STABLE | | √ CON | | 001 | DITIONS TO AVOID: N/A | | | | |
| | UNSTABLE | | CONDITIONS TO AVOID: N/A | | | | | | | |
| INCOMPATABILITY (<i>Materials to avoid</i>): Anhydride, Isocyanate and Organometallic contamination | | | | | | | | | | |
| HAZARDOUS DECOMP | | | | | | | | ce carbon | | |
| monoxide and/or carbon of | dioxide | | | | | | | | | |
| HAZARDOUS POLYMERIZATION: | MAY OCCUR | | | CONDITIONS TO AVOID: N/A | | | | | | |
| | WILL NOT OCCUR | | √ | | | | | | | |
| TOLINILITIZATION. | | | V | | | | | | | |
| | | | | | | | | | | |

SECTION VI – HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION?: yes SKIN?: yes INGESTION?: yes

HEALTH HAZARDS (Acute and Chronic): Prolonged breathing of vapors may cause coughing, shortness of breath, intoxication. Eye contact may cause moderate irritation. Material can affect mucous tissue and/or aggravate mucous membrane dysfunction. Ingestion may cause gastric distress. Excessive ingestion may lead to coma or death.

CARCINOGENICITY: Not identified as a carcinogen by the NTP, IARC Monographs or BY OSHA.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: coughing, dizziness and watery eyes

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Sensitive or inflamed skin may become irritated.

EMERGENCY AND FIRST AID PROCEDURES: If large quantities are ingested, administer warm water and contact a Physician. With eye contact, flush with water. If irritation persists, contact physician.

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all sources of ignition and flush with large quantities of water spray.

WASTE DISPOSAL METHOD: Atomize into an incinerator where appropriate federal, state and local regulations allow.

| SECTION VIII – SPECIAL PROTECTION INFORMATION | | | | | | |
|--|-------------------------------------|---------------|--|--|--|--|
| VENTILATION: | LOCAL EXHAUST: √ | SPECIAL: None | | | | |
| | MECHANICAL (<i>General</i>): None | OTHER: None | | | | |
| PROTECTIVE GLOVE: N/A EYE PROTECTION: Goggles: Use eye bath if eye contact occurs. | | | | | | |
| | | | | | | |
| OTHER PROTECTIVE EQUIPMENT: N/A | | | | | | |
| | | | | | | |

| SECTION | Y _ | SDECIAL | DRECA | PINOITI |
|---------|------------|---------|-------|---------|
| SECTION | _ | SPECIAL | POECA | JIIONS |

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Flammable. Keep away from sparks, flame, or high temperatures

high temperatures.

OTHER PRECAUTIONS: Keep out of the reach of children.

THIS INFORMATION AND RECOMMENDATIONS HEREIN ARE TAKEN FROM SOURCES BELIEVED TO BE ACCURATE AS OF THE DATE, HOWEVER CERTIFIED SAFETY MAKES NO WARRANTY WITH RESPECT TO THE ACCURACY OF THIS INFORMATION OR THE SUITABILITY OF THE RECOMMENDATIONS, AND ASSUMES NO LIABILITY TO ANY USE THEREOF......